

## **Quick Start Guide**

Version 1.0.0

## **PRB-101 Swipe Card Reader Bracket**

IAdea Swipe Card Reader Bracket (SCRB) for mounting on the IAdea WRP-1000 10" All-In-One Smart Signboard







### America

20 Fairbanks, Suite 170 Irvine, CA 92618 USA

#### Taiwan

3F, No. 21, Lane 168, Xingshan Road, Neihu District, Taipei City, 114 Taiwan (ROC)



## **Quick Start Guide**

This quick start guide provides an illustration on how to mount the PRB-101 Swipe Card Reader Bracket (SCRB) onto the left, top or right sides of the IAdea WRP-1000 to enable magnetic stripe card reader integration.


## **Technical Specifications**


| Part                             | Description               |  |  |  |
|----------------------------------|---------------------------|--|--|--|
| Swipe Card Reader Bracket (SCRB) |                           |  |  |  |
| Dimensions                       | 53.6mm x 99.0mm           |  |  |  |
| Material                         | 1.5mm SECC                |  |  |  |
| Net Weight                       | 57.2g                     |  |  |  |
|                                  |                           |  |  |  |
| Compatibility                    | WRP-1000                  |  |  |  |
|                                  | MagTek Super Swipe Series |  |  |  |

## **Product Photo**



## **Technical Dimensions**








**Quick Start Guide** 

#### **Box Contents**

| Item | Part                             | Qty | Description  |
|------|----------------------------------|-----|--|
| Α    | Swipe Card Reader Bracket (SCRB) | 1   | Bracket for mounting swipe card reader   |
| В    | Screw (black M3 x 5 flat head)   | 3   | Securing of swipe card reader to bracket   |
| С    | Screw (black M3 x 8 pan head)    | 2   | Securing WRP-1000 to back cover  |
| D    | Screw (black M2 x 8 pan head)    | 2   | Securing of swipe card reader bracket to WRP-<br>1000 when left or right mounted |
| E    | 3M tape                          | 1   | For securing swipe card reader to bracket when top mounted                       |



## **Tool Preparation**

Tools and items required for the installation:

- Isopropyl wipe
- Philips hand-held screw driver
- Battery-powered drill
- Fine-tip permanent marker
- Phillips drill bit
- Screws for mounting back cover (not included)

#### Mounting and Installation

Significant temperature deviations and changes in elevation or environment can lead to the glass panel of the smart room panel to trap a small amount of moisture. To avoid damage the condensation requires at least 2 to 4 hours to evaporate prior to usage.

#### Different Mounting Locations

The PRB-101 swipe card reader bracket can be mounted onto the WRP-1000 in three different locations. The installation method varies dependant on the mounting location of the bracket.



### **Quick Start Guide**

### Mounting Method 1 (attached lengthwise)





Step 1: Place the WRP-1000 back cover with the bracket at the desired mounting location. Mark the four mounting hole locations.



Step 2: Drill holes in the marked spots then secure the back cover with screws.




Step 3: Connect the magnetic stripe card reader and Ethernet cables to the WRP-1000.



Step 4: Place the WRP-1000 onto the back cover.











Step 6: Remove one side of the tape and affix it to the bracket.







Step 7: Align the SCRB with the WRP-1000 screw hole before securing it to the device using an  $M3 \times 8$  pan head screw.



Step 8: Remove the second side of the tape and affix the Swipe Card Reader to the bracket. Apply adequate force to the swipe card reader to secure it.



Step 9: Conduct cable management as necessary.



Step 10: Installation complete.




### **Quick Start Guide**

### Mounting Method 2 (attached breadthwise, either side)





Step 1: Place the WRP-1000 back cover with the bracket at the desired mounting location. Mark the four mounting hole locations.



Step 2: Drill holes in the marked spots before securing the WRP-1000 back cover with appropriate screws.



Step 3: Secure the swipe card reader to the bracket using two M3 x 5 flat head screws.



Step 4: Remove the screws from the WRP-1000 and secure the bracket to the WRP-1000 using the M2 x 8 pan head screw.




Step 5: Connect the magnetic stripe card reader and Ethernet cable to the WRP-1000.



Step 6: Place the WRP-1000 onto the back cover.









Step 8: Tighten the top screw of device.



Step 9: Conduct cable management as necessary.



Step 10: Installation complete.

Note: PRB-101 mounting video link

Lengthwise: <a href="https://youtu.be/2TAZPH2EZvA">https://youtu.be/2TAZPH2EZvA</a>
Breadthwise: <a href="https://youtu.be/L10gwfR8y74">https://youtu.be/L10gwfR8y74</a>